

# SINGLE POLE DIST. BLOCK, 335 A UL/CSA, CABLE LINE, 11 CABLES LOAD, COPPER

## CATALOG NUMBER

**UD-400A**



## CERTIFICATIONS



## FEATURES

Tinned copper or aluminum block allows for copper or aluminum conductor direct connections, or using ferrule

Screw retaining cover is hinged and removable

Design allows for visual inspection of conductor and confirmation of connection

Modular snap-together blocks for building multi-pole power blocks

Easily clips onto DIN rail or mounts to panel with screws

95% fill ratio

RoHS compliant

Conforms to EN 45545 obtaining an HL3 classification for chapter R23 and HL2 classification for chapter R22

Halogen free

## PRODUCT ATTRIBUTES

Article Number: 569050

Finish: Tinned

Max Current Rating, IEC: 400 A

Max Current Rating, UL/CSA: 335 A

Line Side Connection: Cable

Load Side Connection: 11 Cables

Material: Copper;Thermoplastic

Line Side Max Conductor Size, IEC: 185 mm<sup>2</sup>

Load Side Max Conductor Size, IEC: 35 mm<sup>2</sup>

Max Working Voltage, UL (Vin): 600 V

Max Working Voltage, IEC (Ui): 1,000 VAC/DC

Short Term Withstand Current (I<sub>cw</sub>) 1s: 24.5 kA

Peak Short Circuit Current (I<sub>pk</sub>): 51 kA

Rated Conditional Short-Circuit Current (I<sub>cc</sub>): 24.3 kA

Short Circuit Current Rating (SCCR): 100 kA

Line Side Number of Connections: 1

Line Side Compact Stranded Wire Size: 95 - 185 mm<sup>2</sup>

Line Side Wire Size: 3/0 – 400 kcmil

Load Side Number of Connections: 11

Load Side Stranded Wire Size - Ferrule: (2) 6 - 25 mm<sup>2</sup>;(5) 2,5 - 16 mm<sup>2</sup>;(4) 2,5 - 10 mm<sup>2</sup>

Load Side Wire Size: (2) #10 - #1;(5) #14 - #4;(4) #14 - #6

Load Side Compact Stranded Wire Size: (2) 6 - 35 mm<sup>2</sup>;(5) 2,5 - 16 mm<sup>2</sup>;(4) 2,5 - 10 mm<sup>2</sup>

Enclosure Rating: IP 20

Depth (D): 50 mm

Height (H): 96 mm

Width (W): 49 mm

Unit Weight: 0.400 kg

Certification Details: UL® 1059

Flammability Rating: UL® 94V-0

Complies With: IEC® 60947-7-1

## ADDITIONAL PRODUCT DETAILS

---

Increase the number of outputs with one input using a jumper on blocks with a Max Current Rating, IEC up to 160 A.

Blocks with 1,000 VAC/DC Max Working Voltage, UL are ideal for solar applications.

**Design Guideline for Distribution Blocks, Power Blocks and Power Terminals**

Derating according to Ambient\* Temperature (°C) to maintain working temperature of 85°C

Ambient Temperature (°C)	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°
Derating Coefficient (d)	1	1	1	0.94	0.88	0.82	0.75	0.67	0.58	0.47

\*environment around the terminal blocks inside the enclosure

**WARNING**

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

**Noord-Amerika**

+1.800.753.9221

Optie 1 - de Zorg van de Klant

Optie 2 - Technische Steun

**Europa**

Nederland:

+31 800-0200135

Frankrijk:

+33 800 901 793

**Europa**

Duitsland:

800 1890272

Andere Landen:

+31 13 5835404

**APAC**

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Onze krachtige portefeuille van merken:

**nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER**

© nVent 2022. Alle nVent tekens en emblemen worden bezeten of door de nVent Diensten GmbH of zijn filialen vergunning gegeven. Alle andere handelsmerken zijn het bezit van hun respectieve eigenaars.

nVent reserves het recht specificaties zonder bericht te veranderen.