

EARTHING & NEUTRAL BUSBAR, BRASS, 44 CONNECTIONS

CATALOG NUMBER

EB44



nVent ERIFLEX Connecting, Earthing and Neutral Busbars are used to connect several earthing conductors within a panel and can be used in a variety of different applications including switchgear and control equipment, electrical equipment, for wind and solar power generation and in data centers.

CERTIFICATIONS



FEATURES

Use to connect several earthing conductors within a panel

Chamfered holes allow for easy connections

Mounting slots for universal fixing to copper busbar, directly to rails or spacers

Rigid bar

Mounting kits available for stacking busbars or fixing to DIN rail

RoHS compliant

PRODUCT ATTRIBUTES

Article Number: 568660

Material: Brass

Number of Connections: 44

Conductor Size, IEC: (1) 16 - 35 mm² Stranded;(6) 4 - 16 mm² Stranded;(21) 2.5 - 6 mm² Stranded;(16) 1.5 - 4 mm² Stranded

Ferrule Conductor Size, IEC: (1) 10 - 35 mm²;(6) 2.5 - 16 mm²;(21) 1.5 - 6 mm²;(16) 0.75 - 4 mm²

Conductor Size, UL: (1) #6 - #4 Stranded;(6) #12 - #4 Stranded;(21) #14 - #8 Stranded;(16) #16 - #10 Stranded

Max Current Rating: 250 A

Width: 462 mm

Depth: 13 mm

Height: 13 mm

Thickness: 5 mm

A: 376 mm


B: 43 mm

X: 6.2 x 7 mm

Unit Weight: 0.300 kg

Complies With: IEC® 61439.1

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

Noord-Amerika

+1.800.753.9221

Optie 1 - de Zorg van de Klant

Optie 2 - Technische Steun

Europa

Nederland:

+31 800-0200135

Frankrijk:

+33 800 901 793

Europa

Duitsland:

800 1890272

Andere Landen:

+31 13 5835404

APAC

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Onze krachtige portefeuille van merken:

nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER

© nVent 2022. Alle nVent tekens en emblemen worden bezeten of door de nVent Diensten GmbH of zijn filialen vergunning gegeven. Alle andere handelsmerken zijn het bezit van hun respectieve eigenaars.

nVent reserves het recht specificaties zonder bericht te veranderen.