


## EARTHING & NEUTRAL BUSBAR, BRASS, 36 CONNECTIONS

### CATALOG NUMBER

**EB36**



nVent ERIFLEX Connecting, Earthing and Neutral Busbars are used to connect several earthing conductors within a panel and can be used in a variety of different applications including switchgear and control equipment, electrical equipment, for wind and solar power generation and in data centers.

### CERTIFICATIONS



### FEATURES

Use to connect several earthing conductors

Chamfered holes allow for easy connections

Rigid bar

RoHS compliant

### PRODUCT ATTRIBUTES

Article Number: 568620

Material: Brass

Number of Connections: 36

Conductor Size, IEC: (6) 16 - 35 mm<sup>2</sup> Stranded;(30) 4 - 16 mm<sup>2</sup> Stranded

Ferrule Conductor Size, IEC: (6) 10 - 35 mm<sup>2</sup>;(30) 2.5 - 16 mm<sup>2</sup>

Conductor Size, UL: (6) #6 Solid;(30) #8 - #6 Solid;(6) #6 Stranded;(30) #8 - #6 Stranded

Width: 470 mm

Height: 17 mm

Depth: 15 mm

A: 19 mm


B: 35 mm

X: 16 x 7 mm

Unit Weight: 0.456 kg

Complies With: IEC® 61439.1

## DIAGRAMS



## WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

### Noord-Amerika

+1.800.753.9221

Optie 1 - de Zorg van de Klant

Optie 2 - Technische Steun

### Europa

Nederland:

+31 800-0200135

Frankrijk:

+33 800 901 793

### Europa

Duitsland:

800 1890272

Andere Landen:

+31 13 5835404

### APAC

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Onze krachtige portefeuille van merken:

**nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER**

© nVent 2022. Alle nVent tekens en emblemen worden bezeten of door de nVent Diensten GmbH of zijn filialen vergunning gegeven. Alle andere handelsmerken zijn het bezit van hun respectieve eigenaars.

nVent reserves het recht specificaties zonder bericht te veranderen.