

















IP20

Remote Control Dimmer universal 300W

Technical characteristics

Α.			cti	
AI	rcn	пте	CTL	ıre

Fixing mode	Din-Rail
Main electrical features	
Rated operational voltage Ue	230 V
Frequency	50/60 Hz
Voltage	
Supply voltage	230V +10% / -15%
Fuse	
Fuse	with electronic short-circuit and overload protection
Dimensions	
Depth of installed product	65 mm
Height of installed product	90 mm
Width of installed product	17,5 mm
Power	
Halogen switching capacity 230V	300 W
Power consumed	2,1 W
Power consumption (operation)	2,1 W
Incandescent bulb power	300 W
Total power loss under IN	0,2 W
Capacity	
Number of modules	1
Materials	
RAL colour	RAL 9001 - Cream
Surface appearance	matt
Incandescent bulbs control	
Max. power with incandescent lamps	300 W
Installation, mounting	
Mounting type	din-Rail
Connection	
Connection cross-sect. flexible conductor	1,5 / 6mm²
Connection cross-sect. rigid cable	1,5 / 6mm²
Type of load	universal
Type of connection	with screw
Type of connection	with screw terminals
Equipment	
Dimming principle	automatic load detection
Safety	

Protection index IP IP20 Use conditions Operating temperature -10...45 °C