



SBN325

### 3-pole, 25A Modular Switch

#### Technical characteristics

##### Architecture

Neutral position	without neutral
Number of poles	3 P
Type of pole	3 P

##### Main electrical features

Rated operational voltage Ue	400 V
Frequency	50/60 Hz
Rated current	25 A

##### Voltage

Rated insulation voltage	440 V
Rated impulse withstand voltage	4000 V

##### Dimensions

Depth of installed product	68 mm
Height of installed product	83 mm
Width of installed product	35 mm

##### Power

Total power loss under IN	2,7 W
---------------------------	-------

##### Endurance

Electrical durability at nominal load in AC22 in operating cycles	25000
Number of mechanical operations	200000

##### Capacity

Number of modules	2
-------------------	---

##### Installation, mounting

Tightening torque	1,8Nm
-------------------	-------

##### Connection

Connection cross-sect. flexible conductor	1,5 / 10mm <sup>2</sup>
Connection cross-sect. rigid cable	1,5 / 16mm <sup>2</sup>
Type of connection	with screw

##### Standards

Standard text	IEC 60947-3 IEC/EN 60669-2 IEC/EN 60669-4
European directive WEEE	concerned

##### Safety

Protection index IP	IP20
---------------------	------

##### Use conditions

Operating temperature	-20...50 °C
-----------------------	-------------