

Product data sheet

Item No. 92.232.3060.1

Cable assembly GST18I3K1BS 15H 30SW

geis® Extension cable female - male; length: 3m; type GST18I3;
3-pole;250 V / 16 A; colour of coding: black with black strain-relief;
cable: H05Z1Z1-F 3G1,5, colour: black



| | |
|------------|---------------|
| Item No. | 92.232.3060.1 |
| EAN | 4015573487833 |
| Order Unit | 25 Piece(s) |

Certificates / Approvals



Technical data

General

| | |
|--|--------|
| Rated current | 16 A |
| Rated voltage | 250 V |
| Rated impulse voltage | 4 kV |
| Pollution degree | 2 |
| Mechanical coding | Code 1 |
| Interlockable | Yes |
| Color of coding/ contact carrier | Black |
| Marking of poles | |
| Color of housing inclusive strain relief | Black |

Model

| | |
|---------------------------------|---------------------|
| Number of poles | 3 |
| Nominal cross section conductor | 1.5 mm ² |
| Degree of protection (IP) | IP40 |
| Cable type | S05Z1Z1-F |
| Cable colour | Black |
| Cable diameter | 8 mm |
| Version of cable | Female - male |



| | |
|---------------------|------------------|
| Type of cord set | Connecting cable |
| Version cable end 1 | GST18i3 socket |
| Version cable end 2 | GST18i3 plug |

Material

| | |
|--|------------|
| Surface finish | Tin-plated |
| Halogen free | Yes |
| Continuous temperature of cable | 70 °C |
| Insulation components continuous temperature | 100 °C |

Dimensions

| | |
|--------------|-----|
| Total length | 3 m |
|--------------|-----|

Technical drawing

Buchsteil/female connector **Steckteil/male connector**

Gesamtlänge / total length: $L \pm 3\%$

Kabel/cable: H05Z1Z1-F3G1,5 Halogenfrei/halogen-free
 Farbe/colour: siehe Tabelle/see table

Typ/type: GST18i3K1BS 15H. SW = schwarz/black
 WS = weiß/white
 GR01 = grau/grey
 RT03 = rot/red

Weitere Daten siehe Katalog
 further data see catalog

| .F | Farbe colour | Codierung *X* Buchse female | Codierung *Y* Stecker male | Kabelfarbe cable colour |
|----|---------------|-----------------------------|----------------------------|-------------------------|
| .1 | schwarz black | | | schwarz black |
| .2 | weiß white | | | weiß white |
| .3 | grau grey | | | schwarz black |
| .5 | rot red | | | schwarz black |

| Teile-Nr. part-no. | L | Beispiel (Farbe: schwarz) exempl (colour: black) | Typ type |
|--------------------|--------------------|--|-----------------------|
| 92.232.XX60.F | XX in dm-Schritten | 92.232.1060.1 = 10dm/L= 1000mm | GST18i3K1BS 15H 10SW |
| U2.232.XX60.F | XX in m-Schritten | U2.232.1260.1 = 12 m/L=12000mm | GST18i3K1BS 15H X12SW |
| 92.232.XX80.F | XX in dm-Schritten | 92.232.1080.1 = 10dm/L= 1000mm | |

80.F = spezielle Verpackung und Etikettierung nach A 1960.000
 special packaging and lable according to A 1960.000

Interferenz Size ISO 14224/Tolerance system Size ISO 14224. Toleranz: 20.01. Zeichnung Nr./Drawing No. 92.232.0260.1 01K b

Werkstoff/Material 2.006. Name T

Erstellt/Prepared by: Gezeichnet/Drawn: Geprüft/Checked: Freigegeben/Released: 01.01. 01.01. 01.01. 01.01.

Wieland PRE-ASSEMBLED CABLE KONFEKT-LEITUNG

Buchse/female - Stecker/male 1,5mm
 crimpversion KI 250V halogen-free

WU-FEM-08/916