



TXA606D



**Output module 6x 16A (C)/230V~, KNX**

**Technical characteristics**

**Architecture**

Bus system	yes
Fixing mode	REG

**Functions**

Function	with positioning function for blind and lamella position with safety functions e.g. for wind, rain, alarm with sun shade function
----------	---

**Controls and indicators**

Indicator lamp	yes
----------------	-----

**Connectivity**

Bus system radio frequent	catalog.pageproduct.attribute_boolean.no
---------------------------	--

**Main electrical features**

Rated operational voltage Ue	230 V
Frequency	50/60 Hz
Rated current	16 A

**Dimensions**

Height	90 mm
--------	-------

**Power**

Max. power with electronic transfo.	1200 W
-------------------------------------	--------

**Capacity**

Breaking capacity	16A 250V AC1
-------------------	--------------

**Capacity**

Number of modules	4
-------------------	---

**Materials**

Colour	stone grey
--------	------------

**Incandescent bulbs control**

Max. power with incandescent lamps	2300 W
------------------------------------	--------

**Connection**

Connection cross-sect. flexible conductor	0,75 / 2,5mm <sup>2</sup>
Connection cross-sect. rigid cable	0,75 / 2.5mm <sup>2</sup>
Type of load	C-Load
Type of connection	quick connect
Type of contacts	6NO
Type of connection	with QuickConnect plug-in terminals

**Settings**

Setting	Switching time on change of direction is preset
---------	---

**Safety**

Protection index IP	IP20
---------------------	------

---

**Use conditions**

Operating temperature

-5...45 °C