


## Beacon 50W Mains Voltage - Hi-Spot ES50

BEACON ES50 S/C WHITE 240V  
2041879



### Product features




### PRODUCT OVERVIEW

Product name	BEACON ES50 S/C WHITE 240V
Technology	LED/Halogen
Housing	Aluminium
Mount	Track mounting
Environment	Interior
General application	Hospitality, Museums & Galleries, Retail
ETIM Class	EC001744
E-number FI	4276121
E-number SE	7416257
E-number Norway	3223665
Warranty	5 years
LOR (%)	87
Light colour	N/A
Beam Angle (°)	25
Electrical protection	Class I
Housing colour	White
IP rating	IP20
Product EAN number	5025768418794
Light source included	N/A - Not Applicable

### PHOTOMETRY





## Beacon 50W Mains Voltage - Hi-Spot ES50 BEACON ES50 S/C WHITE 240V 2041879

25°



0.5	0.22	E <sub>01</sub> E <sub>03</sub>	120° 120°	330 154
1.0	0.45	E <sub>01</sub> E <sub>03</sub>	120° 120°	165 77
1.5	0.67	E <sub>01</sub> E <sub>03</sub>	120° 120°	110 51
2.0	0.89	E <sub>01</sub> E <sub>03</sub>	120° 120°	83 39
2.5	1.12	E <sub>01</sub> E <sub>03</sub>	120° 120°	66 31
3.0	1.34	E <sub>01</sub> E <sub>03</sub>	120° 120°	55 26

Distance [m] Cone diameter [m] Illuminance [lx]  
C0 - C180 (Half beam angle: 25.2°)



0.5	0.43	E <sub>01</sub> E <sub>03</sub>	219° 219°	260 110
1.0	0.80	E <sub>01</sub> E <sub>03</sub>	219° 219°	130 55
1.5	1.21	E <sub>01</sub> E <sub>03</sub>	219° 219°	87 37
2.0	1.61	E <sub>01</sub> E <sub>03</sub>	219° 219°	65 28
2.5	2.01	E <sub>01</sub> E <sub>03</sub>	219° 219°	50 22
3.0	2.41	E <sub>01</sub> E <sub>03</sub>	219° 219°	40 18

Distance [m] Cone diameter [m] Illuminance [lx]  
C0 - C180 (Half beam angle: 43.8°)

### TECHNICAL DRAWINGS

