

S-D2WF series

Loose Flanges DIN 2642 PN10



| Steel | 1.4571 | b | 1.4301 | b | S | Number of bolt holes | | | | | |
|-------|--------|----|--------|------|---|----------------------|-----|-----|-----|----|-----|
| F2VUR | F2VV8 | 14 | F2VVQ | 11.5 | 3 | 4 | 10 | 90 | 19 | 14 | 60 |
| F2VUS | F2VV9 | 14 | F2VVR | 12.0 | 3 | 4 | 15 | 95 | 24 | 14 | 65 |
| F2VUT | F2VVA | 14 | F2VVS | 13.5 | 3 | 4 | 20 | 105 | 30 | 14 | 75 |
| F2VUU | F2VVB | 16 | F2VVT | 16.0 | 3 | 4 | 25 | 115 | 37 | 14 | 85 |
| F2VUV | F2VVC | 16 | F2VVU | 17.0 | 3 | 4 | 32 | 140 | 46 | 18 | 100 |
| F2VUW | F2VVD | 16 | F2VVV | 18.0 | 3 | 4 | 40 | 150 | 54 | 18 | 110 |
| F2VUX | F2VVE | 16 | F2VVW | 20.0 | 3 | 4 | 50 | 165 | 65 | 18 | 125 |
| F2VUY | F2VVF | 16 | F2VVX | 21.0 | 4 | 4 | 65 | 185 | 81 | 18 | 145 |
| F2VUZ | F2VVG | 18 | F2VVY | 22.0 | 4 | 8 | 80 | 200 | 94 | 18 | 160 |
| F2VV2 | F2VVH | 18 | F2VVZ | 23.0 | 4 | 8 | 100 | 220 | 119 | 18 | 180 |
| F2VV3 | F2VVJ | 18 | F2VV2 | 25.0 | 5 | 8 | 125 | 250 | 145 | 18 | 210 |
| F2VV4 | F2VVK | 18 | F2VV3 | 27.0 | 5 | 8 | 150 | 285 | 173 | 22 | 240 |
| F2VV5 | F2VVM | 20 | F2VV4 | 31.0 | 6 | 8 | 200 | 340 | 225 | 22 | 295 |
| F2VV6 | F2VVN | 22 | F2VV5 | 31.0 | 6 | 12 | 250 | 395 | 279 | 22 | 350 |
| F2VV7 | F2VVP | 26 | F2VV6 | 34.0 | 6 | 12 | 300 | 445 | 329 | 22 | 400 |